

559592

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
7 October 2004 (07.10.2004)

PCT

(10) International Publication Number  
**WO 2004/085070 A1**

(51) International Patent Classification<sup>7</sup>: **B02C 7/14**,  
G01B 7/14, D21D 1/30

(21) International Application Number:  
PCT/SE2004/000339

(22) International Filing Date: 9 March 2004 (09.03.2004)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:  
0300794-5 24 March 2003 (24.03.2003) SE

(71) Applicant (for all designated States except US): **DAPROX AB** [SE/SE]; P.O. Box 120, S-127 23 Skärholmen (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **ÅKERBLOM, Bengt** [SE/SE]; Vårby Allé 23, S-143 40 Vårby (SE).

(74) Agent: **ALBIHNS STOCKHOLM AB**; P.O. Box 5581, S-114 85 Stockholm (SE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A METHOD AND A SENSOR DEVICE FOR MEASURING THE DISTANCE BETWEEN A STATOR AND AN OPPOSING ROTOR



(57) Abstract: A sensor device for measuring distance between a stator and a rotor in a machine is of the magnetic type and is intended to be mounted in the stator in order to interact with an opposing surface on the rotor. A sensor body (10) can be moved axially in a housing (11) mounted in the stator by means of an operating mechanism (13) and has a stop (16) at a predetermined distance (e) from its end surface designed to interact with a corresponding stop (17) inside the housing. This distance (e) exceeds the distance (d) between the stop (17) in the housing and the end of the sensor body (10) by a predetermined distance (c) when the sensor body is in its normal measuring position. These stops (16, 17) make possible a particularly accurate calibration of the sensor device.

WO 2004/085070 A1

## A METHOD AND A SENSOR DEVICE FOR MEASURING THE DISTANCE BETWEEN A STATOR AND AN OPPOSING ROTOR

### Technical field

The present invention relates to a method for measuring distance  
5 according to the preamble to Claim 1, and to a sensor device for  
measuring distance according to the preamble to Claim 3.

### Background art

In refiners designed for the manufacture of paper pulp, the size of the  
10 grinding gap between a stator and a rotor changes during operation as a  
result of wear on the grinding segments on the stator and rotor that face  
each other. For reasons of quality, it is desirable to have good control over  
the size of the grinding gap and to be able to change the size of the  
grinding gap in order, for example, to be able to compensate for wear.  
15 Refiners of this type have normally long operating periods, often several  
months, for which reason monitoring of the size of the grinding gap should  
be able to be carried out during operation.

In order to measure the size of the grinding gap, it is customary to use  
20 sensors of the magnetic type that are positioned stationary in the stator,  
with the end surface of the measuring head on a level with the surface of  
the grinding segments. For sensor calibration, the rotor is moved first  
axially in the direction towards the stator, while rotating and during idle  
running, until the grinding segments of both stator and rotor come into  
25 contact with each other. In this state, the sensor is zeroed. By then moving  
the rotor back a predetermined distance, the sensor can be calibrated. One  
of the disadvantages of such a method is that it can only be used on  
machines where the rotor can be operated with precision, as otherwise the  
wear caused by the zero-setting can be considerable and, in addition, the  
30 calibration and monitoring of the sensor can only be carried out during idle  
running.

- 2 -

A better method has proved to be to mount a sensor of the magnetic type in the stator in such a way that it can be moved, in order to be able to bring the sensor into contact with the rotor during calibration without needing to move the rotor axially. By this means, the change in position of the sensor is recorded close to the end of the sensor facing away from the grinding segment, thus at a large distance from the end surface of the measuring head. This results in a relatively large distance between the measurement position and the end surface of the sensor, with consequent difficulties in ensuring the required precision in the measurements, as during operation the sensor is often subjected to a change in length due to temperature variations. Against this background, there is a need for improved solutions within this field.

#### Object of the invention

The object of the invention is to make it possible to determine with increased precision the distance between stator and rotor in machines of the stated type. Another object is to achieve a simple solution.

#### Disclosure of invention

The object of the invention is achieved by a method with characteristics according to Claim 1 and also by means of a sensor device with characteristics according to Claim 3.

By utilizing a stop located close to the measuring end of the sensor body, it is possible to obtain a movement of the sensor body that is well-defined as far as distance is concerned at the end where measurement takes place, and by this means a more precise calibration can be carried out than what was possible previously.

Additional characteristics and advantages of the solution according to the invention will be apparent from the description and other claims.

The invention will be described in greater detail in the following with reference to an embodiment illustrated in the drawings.

### Description of drawings

In the drawings:

- Figure 1 shows a schematic view of a machine provided with a device  
5 according to the invention,  
Figure 2 shows a detail of a sensor mounting in the stator on a machine  
according to Figure 1, and  
Figure 3 shows an enlarged section of Figure 2.

### 10 Modes for carrying out the invention

- Figure 1 shows schematically a machine 1 of the refiner type designed for  
paper pulp manufacture, in which the invention is utilized. This machine is  
provided with a rotor 3, mounted in a framework 2 in such a way that it can  
rotate, which rotor is driven by a motor 4 and can also be moved axially in  
15 a direction to and from a stator 5 in order to adjust the size of a grinding  
gap 6 between the rotor 3 and the stator 5. For monitoring the size of the  
grinding gap 6 at least one sensor device 7 is mounted in the stator 5, with  
a sensor that is of the magnetic type and operates suitably according to the  
reluctance principle. This type of sensor is well known to experts within the  
20 field. There can suitably be two or more sensor devices 7 distributed  
around the stator 5.

- As shown in greater detail in Figure 2, both the rotor 3 and the stator 5 are  
provided with a suitable number of grinding segments 8, 9 that have a  
25 surface suitable for grinding paper pulp and that are mounted in a ring on  
the rotor and stator. These grinding segments 8, 9 are subjected to wear  
during operation and are therefore suitably mounted in such a way that  
they can be replaced. On at least one of the grinding segments 9, the  
stator 5 is provided with a sensor device 7 in which a sensor body 10 is  
30 arranged in such a way that it can be moved axially in a fixed housing 11  
mounted in the stator, which housing can, for example, be screwed into the  
stator 5 or mounted in some other way. In this case, the housing 11 is  
screwed by an end part into a holder 12 in the stator 5 for the grinding  
segment 9, but other ways of attaching the housing 11 are of course

- 4 -

possible. An operating mechanism 13 for achieving axial movement of the sensor body 10 within the housing 11 is positioned on the end of the housing 11 facing away from the rotor 3. The operating mechanism 13 can suitably comprise an electric motor 14, which is connected to the sensor  
5 body 10 via a transmission and a roller screw, suitably with a fine pitch. By this means, operation of the sensor body 10 via the motor 14 can be carried out at a distance from the stator 5. It is, of course, also possible to use a manually-operated mechanism. Such operating mechanisms are known in various forms and are therefore not described here in greater  
10 detail. Movement of the sensor body 10 relative to the housing 11 is determined by means of a measuring device 15 arranged in the housing 11 in the vicinity of the operating mechanism 13.

Figure 3 shows that an end of the housing 11 is screwed into the holder 12  
15 and makes contact with the grinding segment 9 which has the thickness a. The sensor body 10 narrows at the front to a measuring end 10a, with a transitional part designed as a stop 16, which measuring end 10a passes through the housing 11 and the grinding segment 9, and the end surface of which is on a level with the surface of the grinding surface 9 in the drawing.  
20 The inside of the end of the housing 11 forms in turn a stop 17 which is at a distance b from the end of the housing 11, and which is intended to interact with the stop 16 on the sensor body 10 in order to limit the axial movement of the sensor body 10 in the direction towards the rotor 3. In the position shown, the two stops 16 and 17 are a distance c apart and, when  
25 they have been brought into contact with each other, the measuring end 10a can thus protrude a distance c beyond the grinding segment 9, in the position shown by broken lines.

In order to ensure that, in the position when they are in contact with each  
30 other, the two stops 16 and 17 actually make good contact and can thereby define with precision the positions of the sensor body 10 and the housing 11, the stop 16 has been provided with teeth 18, the tips of which point towards the stop 17. By this means, even if impurities manages to penetrate into the space between the two stops 16 and 17, for example via

- 5 -

the gap around the measuring end 10a, the tips of the teeth can penetrate through these impurities and make contact with the stop 17. The number of teeth 18 and their shape can, of course, vary according to need and requirements. If required, the stop 17 can have a similar design.

5

During the use of the sensor device 7, the measuring end 10a on the sensor body 10 and the grinding segment 9 will be worn down at the same rate, for which reason the distance  $c$  between the two stops 16 and 17 will remain constant. This makes it possible to monitor the position of the end surface of the measuring end 10a with increased precision, as follows:

In association with mounting the sensor device 7, the end surface of the measuring end 10a is placed on a level with the surface of the grinding segment 9, whereby the stops 16 and 17 are thus a distance  $c$  apart. The measuring device 15 indicates hereby a particular position of the sensor body 10 relative to the housing 11. By thereafter moving the sensor body 10 to make contact between the stops 16 and 17, with the rotor 3 and the stator 5 at a sufficiently large distance apart, a correlation is obtained between the recorded movement and the actual movement  $c$  of the end surface of the measuring end 10a. Thereafter the sensor body 10 is moved back to the initial position.

When the machine 1 is to be put into use, the measuring head 10a is moved to make contact with the grinding segment 8 on the rotor 3, which hereby rotates. This provides a contact position for the sensor body 10. In order to determine in a reliable way when there is contact between the measuring end 10a and the grinding segment 8 on the rotor 3, an accelerometer 19 for example can be used, placed on the sensor body 10 near the operating mechanism 13. This records the vibrations that arise upon contact and emits a corresponding signal that makes it possible to stop the forward movement of the sensor body 10 in time. If required, the housing 11 can also be provided with an accelerometer in order to record such contact vibrations. After contact has been established with the grinding segment 9, the sensor body 10 is moved back to its initial position.

- 6 -

On the basis of the previously established correlation between the actual and recorded movement of the sensor body 10, the distance between the stator and the rotor can now be determined with precision, which makes possible a precise adjustment of the size of the grinding gap 6.

5

In order to ensure continued precision, it is possible, after a period of operation, to move the rotor and stator apart sufficiently for the calibration carried out in association with the mounting of the sensor device 7 to be able to be repeated. By this means, any correction that is required of the previously used correlation between the recorded and actual movement of the end surface of the measuring end 10a can be carried out. After the checking has been carried out, normal operation can be resumed.

The size of the grinding gap 6 is often approximately 2 mm or less, and in order to ensure that requisite measurements according to the above can be carried out, the distance c between the two stops 16 and 17 can suitably amount to at least approximately 3 mm.

Bearing in mind that a machine 1 of the type described is large, with a diameter of rotor and stator of the order of 1.5 - 2 m, and the rotor 3 rotates at a speed of the order of 1500 - 1800 rpm, it is important that the size of the grinding gap 6 can be checked accurately. Several sensor devices 7 can therefore suitably be used in order to check that the grinding gap 6 is the same size all round. The grinding segments 8, 9 can be worn down at such a rate that a rotor movement of approximately 2 mm per 2000 hours is required to maintain the size of the gap, and it is therefore obvious that it is necessary to be able to monitor the size of the gap with precision in order to be able to make suitable adjustments to the position of the rotor in order to maintain a particular product quality.

30

By means of arranging a reference position for the movement of the sensor body 10 at the actual measuring end 10a of the sensor body according to the invention, the risk is reduced of incorrect measurements as a result of the influence of temperature and a consequent increase in length of the

- 7 -

sensor body 10 between the end surface of the measuring head 10a and the position near the operating mechanism 13 where the movement of the sensor body 10 is recorded.



Claims

1. A method for measuring distance between a stator (5) and an opposing rotor (3) in a machine, in particular a refiner designed for the manufacture of paper pulp, where the stator is provided with at least one sensor device (7) of the magnetic type which is intended to interact with an opposing surface on the rotor, and where a sensor body (10) can be moved axially in a housing (11) mounted in the stator, with the sensor device being calibrated by the sensor body being moved a distance in the direction towards the rotor and the size of this movement being related to the signal value from the sensor device, characterized in that the movement is made so large that contact is made between stops (16, 17) in the sensor device arranged at a predetermined distance (c) apart and interacting with each other, with one stop (16) being arranged on the sensor body (10) at a predetermined distance (e) from the end surface of the measuring end (10a) of the sensor body (10), which distance (e) is considerably smaller than the length of the sensor body (10), and the second stop (17) being arranged in the housing (11).
2. A method according to Claim 1, characterized in that the movement is commenced from a position where the end of the sensor body (10) is on a level with a grinding segment (9) facing towards the rotor (3).
3. A sensor device for measuring distance between a stator (5) and an opposing rotor (3) in a machine, in particular a refiner designed for the manufacture of paper pulp, where the sensor device (7) is of the magnetic type and is intended to be mounted in the stator in order to interact with an opposing surface on the rotor, and where a sensor body (10) can be moved axially in a housing (11) intended to be mounted in the stator and is connected to an operating mechanism (13) for axial movement of the sensor body relative to the housing, characterized in that the sensor body (10) has a stop (16) at a predetermined distance (e) from the end surface of its measuring end (10a), which distance (e) is considerably smaller than the length of the sensor body (10), which stop (16) is designed to interact

with a corresponding stop (17) inside the housing (11), and in that this distance (e) exceeds the distance (d) between the stop (17) in the housing and the end surface of the measuring end (10a) of the sensor body by a predetermined distance (c) when the sensor body is in its normal




5 measuring position in the stator.

4. A sensor device according to Claim 3, characterized in that the stop (16) in the sensor body is provided with teeth (18), the tips of which point towards the stop (17) in the housing.

10

5. A sensor device according to Claim 3 or 4, characterized in that the stop (17) in the housing is essentially in the shape of a ring and is arranged at the end of the housing (11).

15 6. A sensor device according to any one of Claims 3-5, characterized in that the distance (c) between the two stops (16, 17) is at least the same size as the grinding gap (6) between the rotor and the stator when the sensor body (10) is in its normal measuring position.



## INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 2004/000339

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B02C 7/14, G01B 7/14, D21D 1/30

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B02C, G01B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 0171276 A1 (D/A PRODUCTION AB), 27 Sept 2001 (27.09.2001), whole document  --	1-6
A	EP 0640395 A1 (ANDRITZ SPROUT-BAUER, INC.), 1 March 1995 (01.03.1995), abstract  --	1-6
A	US 3898562 A (D.M.MIZIKAR ET AL), 5 August 1975 (05.08.1975), column 3, line 47 - column 4, line 10, figure 1  -- -----	1-6



Further documents are listed in the continuation of Box C.



See patent family annex.

## \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

18 May 2004

Date of mailing of the international search report

14-06-2004

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer

Henrik Eriksson/itw  
Telephone No. +46 8 782 25 00

**INTERNATIONAL SEARCH REPORT**  
Information on patent family members

30/04/2004

International application No.

PCT/SE 2004/000339

WO	0171276	A1	27/09/2001	AU	5857100	A	02/01/2001
				CA	2373820	A	27/09/2001
				DE	10084696	T	29/05/2002
				EP	1192408	A	03/04/2002
				JP	2003502738	T	21/01/2003
				JP	2003528302	T	24/09/2003
				SE	520322	C	24/06/2003
				SE	0001031	A	24/09/2001
				US	6657427	B	02/12/2003
				US	2002158628	A	31/10/2002
<hr/>							
EP	0640395	A1	01/03/1995	AT	183409	T	15/09/1999
				CA	2119598	A	26/02/1995
				DE	69420092	D	00/00/0000
				FI	942485	A	26/02/1995
				JP	7083606	A	28/03/1995
				NO	940915	A	27/02/1995
				US	5691636	A	25/11/1997
<hr/>							
US	3898562	A	05/08/1975	BR	7503162	A	27/04/1976
				CA	1037286	A	29/08/1978
				CH	580319	A	30/09/1976
				DE	2521147	A,B,C	18/12/1975
				FR	2273346	A,B	26/12/1975
				GB	1505675	A	30/03/1978
				IT	1037670	B	20/11/1979
				JP	1025142	C	18/12/1980
				JP	51000982	A	07/01/1976
				JP	55015648	B	25/04/1980
				NL	173100	C	01/12/1983
				NL	7505536	A	02/12/1975